Accu Sync™

Gain unparalleled pressure regulation for any Hunter valve.



Operating Specifications:

- Regulation from 1.4 to 7.0 bar; 140 to 700 kPa
- Static pressure: 10 bar; 1,000 kPa
- Required dynamic pressure differential: 1.0 bar; 100 kPa
- Works with AC- and DC-latching solenoids
- Works with any Hunter valve
- Warranty period: 2 years

Accu-Sync Valve Recommended Flow Range

	Flow	
Valve	**m³/hr**	**l/min**
PGV-100/101	4.5 - 9.1	76 - 151
PGV-151	4.5 - 28	76 - 454
PGV-201	9.1 - 34	151 - 568
ICV-101	3.4 - 9.1	57 - 151
ICV-151	4.5 - 34	76 - 568
ICV-201	9.1 - 45	151 - 757
ICV-301	34 - 68	568 - 1,136
IBV-101	3.4 - 9.1	57 - 151
IBV-151	4.5 - 34	76 - 568
IBV-201	9.1 - 45	151 - 757
IBV-301	34 - 68	568 - 1,136

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterirrigation.com/en-metric/irrigation-product/valves/accu-synctm
032726