SPRAY ACCESSORIES

Spray accessories provide additional flexibility for installation and maintenance of spray systems.

SJ SWING JOINTS

Features
- Unique swivel ells on both ends for easy installation in any configuration.
- Swing joints are built with air-tight connection points for long-term reliability.

Models
- SJ-506: ½" threaded x 15 cm length
- SJ-7506: ½" x ¾" threaded x 15 cm length
- SJ-706: ¾" threaded x 15 cm length
- SJ-512: ½" threaded x 30 cm length
- SJ-7512: ½" x ¾" threaded x 30 cm length
- SJ-712: ¾" threaded x 30 cm length

Operating Specifications
- Pressure-rated to 10 bar; 1000 kPa
- Warranty period: 2 years



SJ Swing Joint
15 cm or 30 cm links

HUNTER SPIRAL BARB ELBOWS

Features
- Improved bigger, stronger design
- Compatible with FlexSG and other brands for a customised swing joint
- Spiral to barb design for easier installation
- Acetal material for sharp barbs

Models
- HSBE-050: ½" male x spiral barb elbow
- HSBE-075: ¾" male x spiral barb elbow

Operating Specifications
- Operating pressure: Up to 5.5 bar; 550 kPa
- Warranty period: 2 years



Spiral Barb Elbows
HSBE-050, HSBE-075

FLEXSG TUBING

Features
- Engineered to resist kinking
- Textured for easy grip
- Linear low-density polyethylene material
- Meets ASTM D2104, D2239, D2737

Models
- FLEXSG: 30 m roll
- FLEXSG-18: 45 cm pre-cut lengths

Operating Specifications
- Operating pressure: up to 5.5 bar; 550 kPa
- Warranty period: 2 years



FLEXSG Tubing
30 m and 45 cm pre-cut lengths
Inside diameter: 1.2 cm

PRO-SPRAY SHUTOFF CAP

Features
- Caps off the Pro-Spray for maintenance or drip conversions
- Maintains a clean look to the landscape

Models
- 213600SP



Pro-Spray Shutoff Cap
P/N 213600SP

SHUTOFF NOZZLE

Features
- Easy shutoff for spray systems
- Allows heads to pop-up for easy visibility
- Use with Pro-Spray and PS Ultra models

Models
- 916400SP



Shutoff Nozzle
P/N 916400SP

SWING JOINTS

With swivel ells on both ends, SJ Swing Joints easily adjust sprinklers to proper height and position in any configuration.

KEY BENEFITS

- Strength, longevity and contamination resistance
  - Prefabricated PVC design with O-ring seals
- Configurations to meet every installation requirement
  - Available in all popular inlet and outlet configurations
  - Choose from 20 cm, 30 cm, or 46 cm lay arm lengths
  - Single top-out or triple top-out designs

Swing Joints
HSJ-0 = Model ¾"
HSJ-1 = Model 1" (25 mm)
HSJ-2 = Model 1¼" (30 mm)
HSJ-3 = Model 1½" (40 mm)



SWING JOINT – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4 + 5

1 Model

HSJ-0 = ¾" commercial Swing Joint

HSJ-1 = 1" (25 mm) heavy-duty Swing Joint

HSJ-2 = 1¼" (30 mm) heavy-duty Swing Joint

HSJ-3 = 1½" (40 mm) heavy-duty Swing Joint

2 Inlet Type (from pipe fitting)

3 = Male NPT



4 = Male Acme*



6 = Male BSP**



7 = Spigot, 10 cm long**



M = Main Acme H-connection ***

P = Main Acme V-connection

* *Not available in HSJ-0 or HSJ-3. Use "M" inlet for HSJ-3.*
** *Not available in HSJ-0.*
*** *Horizontal connection reduces from 40 mm Acme to Swing Joint size*

3 Outlet Type (to sprinkler inlet)

0 = Male Acme



2 = Male NPT



5 = Male BSP *(not available in HSJ-0)*



6 = Enlarging to 1½" (40 mm) male BSP*

8 = Enlarging to 1½" (40 mm) male Acme*

A = Enlarging/reducing to 30 mm male Acme**

* *Not available in HSJ-0 or HSJ-3*
** *Not available in HSJ-0 and HSJ-2*

4 Outlet Style

2 = Single top-out



4 = Triple top-out



5 Lay Length

8 = 20 cm lay arm*

12 = 30 cm lay arm



18 = 46 cm lay arm**

* *HSJ-0 only*
** *Not available in HSJ-0*

Example:
HSJ-1-3-2-2-12 = HSJ 1" (25 mm) heavy-duty Swing Joint, 1" (25 mm) NPT inlet, 1" (25 mm) male NPT single top-out outlet, 30 cm lay arm length

SnapLok is a trademark of LASCO Fittings Inc.