MWS

Sensor: **Wind, Rain, Freeze**

This all-in-one wind, rain, and freeze sensor prevents water waste when any sensor triggers a stop to the system.

KEY BENEFITS

- Compact sensor with built-in wind, rain, and freeze sensors
- Installs easily on automatic irrigation systems with limited adjustment
- Set wind actuation speed shutdown from 13 to 38 kph
- Set system shutdown from 3 mm to 19 mm of rainfall
- Automatically shuts off system when temperatures fall below 3°C
- Mounts: Slip fits over 5 cm PVC pipe or attaches to 1 cm conduit with adapter (included)

OPERATING SPECIFICATIONS

- Switch rating (24 VAC): 5 A maximum
- Wind vane diameter: 13 cm
- Reset speed: 13 to 38 kph
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years



MWS
Height: 20 cm
Wind vane diameter: 13 cm



MWS-FR
Height: 20 cm
Wind vane diameter: 13 cm

MWS	
Model	**Description**
MWS	Weather station combines wind and rain sensors
MWS-FR	Weather station combines wind and rain sensors with a freeze sensor

Compatible with:



Waterproof Wire Connector

SENSORS

FREEZE-CLIK™

Sensor: **Freeze**

Use this sensor to stop sprinklers from running during a freeze event and protect landscapes, walkways, and roadways from icy conditions.

KEY BENEFITS

- Automatically shuts off irrigation system when temperatures fall below 3°C
- Installs easily on automatic irrigation systems with no adjustments needed
- Use with other sensors to enhance overall efficiency of irrigation systems

Note: Not intended for agricultural applications

SPECIFICATIONS

- Switch rating (24 VAC): 5 A
- Includes 7 m of 0.5 mm^2 sheathed, two-conductor, UL-approved wire
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

FREEZE-CLIK	
Model	**Description**
FREEZE-CLIK	Wired freeze sensor



FREEZE-CLIK
Height: 5 cm
Length: 11 cm
Width: 3.5 cm

Compatible with:



Waterproof Wire Connector

WIND-CLIK™

Sensor: **Wind**

This sensor keeps water coverage efficient and pedestrian paths and roadways safe by shutting down irrigation when wind speeds increase.

KEY BENEFITS

- Shuts off irrigation when winds are high
- Works well with fountains to eliminate overspray in windy conditions
- Installs easily on automatic irrigation systems with quick adjustments
- Compatible with most normally open or normally closed irrigation controllers

SPECIFICATIONS

- Switch rating (24 VAC): 5 A maximum
- Wind vane diameter: 13 cm
- Reset speed: 13 to 38 kph
- Mounts: Slip fits over 5 cm PVC pipe or attaches to 1 cm conduit with adapter (included)
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

WIND-CLIK	
Model	**Description**
WIND-CLIK	Wired wind sensor



WIND-CLIK
Height: 10 cm
Wind vane diameter: 13 cm

Compatible with:



Waterproof Wire Connector